

AM Security Labels

An Alternative to Sensormatic UltraStrip® III (DR) Labels



- Roll format well suited for automated high-speed application
- Compatible with TYCO/Sensormatic and other Acousto-Magnetic (AM) 58 KHz EAS Systems and Deactivators
- Comparable EAS System Detection and Deactivation performance to TYCO/Sensormatic UltraStrip III (DR) Labels

LABEL REFERENCE	AM-AMK2MPW, 7.5k (white) / AM-AMK2MBL, 7.5k
ROLL QUANTITY	7500
COVER OF LABEL	PLAIN WHITE / BLACK / FOOD SAFE
LABEL LENGTH	44.5 MM (1.75 INCHES)
LABEL WIDTH	11.3 MM (0.44 INCHES)
LABEL + SUPPORT LINER WIDTH	48.36 MM (1.9 INCHES)
LABEL THICKNESS (INCLUDING LINER)	1.99 MM (0.078 INCHES)
LABEL THICKNESS (EXCLUDING LINER)	1.92 MM (0.075 INCHES)
SPACE BETWEEN 2 LABELS	3.38 MM (0.13 INCHES)
LABEL REPEAT	14.68 MM (0.58 INCHES)
MAXIMUM EXTERNAL ROLL DIAMETER	530 MM (20.8 INCHES)
DIAMETER OF CORE	76.2 MM (3 INCHES) OR 152.4 MM (6 INCHES)
LABEL FREQUENCY	58 KHz
LABEL HOUSING	PLASTIC
ANTENNA	TRIPPLE RESONATOR
DEACTIVATABLE	YES
WARRANTY	1 YEAR FROM DATE OF MANUFACTURE
LABEL STORAGE	TEMP. NOT TO EXCEED 122 FOR 96 HOURS AT 80% RH
LABELS PER BOX	30,000 (4 ROLLS)
BOX WEIGHT	39.18 LBS.
BOXES PER PALLET	16

ALL-TAG

1155 Broken Sound Parkway NW, Unit E • Boca Raton, Florida 33487 USA
Telephone: 561-998-9983 • Fax: 561-998-4897 E-mail: info@all-tag.com • Website: www.all-tag.com